



# HYLOAD WARRANTY APPLICATION

PLACE "X" NEXT TO WARRANTY REQUESTED

Material Only				Labor & Material				NDL				NDL Including Hail			
X	Term	Cost/Ft <sup>2</sup>	Min Fee	X	Term	Cost/Ft <sup>2</sup>	Min Fee	X	Term	Cost/Ft <sup>2</sup>	Min Fee	X	Term	Cost/Ft <sup>2</sup>	Min Fee
	10	\$0.06	\$600		10	\$0.09	\$900		10	\$0.11	\$1,100		10	Not Available	
	15	\$0.08	\$800		15	\$0.12	\$1,200		15	\$0.13	\$1,300		15	\$0.18	\$1,800
	20	\$0.10	\$1,000		20	\$0.14	\$1,400		20	\$0.15	\$1,500		20	\$0.20	\$2,000

**WARRANTY FEE:**

Cost/Ft<sup>2</sup> x \_\_\_\_\_ Ft<sup>2</sup> = \$ \_\_\_\_\_ Please note minimum fee if applicable.

Hyload's Limited Warranty is strictly limited to the terms and conditions set forth in the written warranty provided to the Building Owner identified below.

**PAYMENT MUST ACCOMPANY APPLICATION**

**PROJECT:** \_\_\_\_\_ Completion Date \_\_\_\_\_

Area Name or Designation \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Contact(s) \_\_\_\_\_ Phone \_\_\_\_\_ Fax \_\_\_\_\_

**BUILDING OWNER:** \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Contact(s) \_\_\_\_\_ Phone \_\_\_\_\_ Fax \_\_\_\_\_

**ARCHITECT/CONSULTANT:** \_\_\_\_\_

Firm \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Contact(s) \_\_\_\_\_ Phone \_\_\_\_\_ Fax \_\_\_\_\_

**QUALITY CONTROL PERFORMED BY:** \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

President/Owner \_\_\_\_\_ Job Foreman \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_

**ROOFING CONTRACTOR:** \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

President/Owner \_\_\_\_\_ Job Foreman \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_



**HYLOAD MATERIALS WERE PURCHASED FROM:**

Distributor/Representative \_\_\_\_\_ Contact \_\_\_\_\_

**PROJECT SPECIFICATIONS PREPARED BY:**

Architect \_\_\_\_\_ Consultant \_\_\_\_\_ Owner \_\_\_\_\_ Other \_\_\_\_\_

**HYLOAD SPECIFICATION NO.:** \_\_\_\_\_

**TYPE OF PROJECT:** New Construction \_\_\_\_\_ Replacement \_\_\_\_\_ Retrofit \_\_\_\_\_

**USE OF STRUCTURE:** \_\_\_\_\_

**DECK TYPE:** \_\_\_\_\_

**DECK CONDITION:** \_\_\_\_\_

**VAPOR RETARDER SPECIFIED:** \_\_\_\_\_

**VAPOR RETARDER ADHESION TO DECK:** \_\_\_\_\_

**INSULATION SPECIFIED?**

Yes \_\_\_\_\_ No \_\_\_\_\_  
Type \_\_\_\_\_

**BEVELED INSULATION SPECIFIED?**

Yes \_\_\_\_\_ No \_\_\_\_\_  
Type \_\_\_\_\_ Adhesion \_\_\_\_\_ Layer No. \_\_\_\_\_

**BASE SHEET:**

Type \_\_\_\_\_ Adhesion \_\_\_\_\_

**PLY SHEET BUILD-UP:**

Ply No. \_\_\_\_\_ Type \_\_\_\_\_ Adhesion \_\_\_\_\_ Manufacturer \_\_\_\_\_ Type \_\_\_\_\_

Ply No. \_\_\_\_\_ Type \_\_\_\_\_ Adhesion \_\_\_\_\_ Manufacturer \_\_\_\_\_ Type \_\_\_\_\_

Ply No. \_\_\_\_\_ Type \_\_\_\_\_ Adhesion \_\_\_\_\_ Manufacturer \_\_\_\_\_ Type \_\_\_\_\_

Ply No. \_\_\_\_\_ Type \_\_\_\_\_ Adhesion \_\_\_\_\_ Manufacturer \_\_\_\_\_ Type \_\_\_\_\_

**FLASHINGS:**

Note: Prime all metal surfaces with asphalt primer prior to adhering asphaltic materials to them.

**TYPES OF METAL DETAILS USED ON PROJECT:**

Metal Edge \_\_\_\_\_ Thru-Wall Counterflashing \_\_\_\_\_ Coping Cap \_\_\_\_\_ Gutter Detail \_\_\_\_\_  
Pressure Bar (to Masonry) \_\_\_\_\_ Pressure Bar (to Metal) \_\_\_\_\_ Expansion Joint \_\_\_\_\_  
Tie in to Existing Roof \_\_\_\_\_ Other(s) \_\_\_\_\_



**HYLOAD MEMBRANE USED:** \_\_\_\_\_

No. of Square Feet: \_\_\_\_\_

Adhesion: \_\_\_\_\_

Fields laps adhered by:                      Asphalt                      Hot Air Weld                      Chemical Weld

**ACCESSORIES:**

List any additional products planned for use with the Hyload products installed. Include expansion joints, boot type flashings, sealants, etc.

\_\_\_\_\_

**NOTE:**

On asphalt adhered laps, the entire roof must be flood coated with hot asphalt at a rate of 60 lbs. per square minimum and aggregate embedded at a minimum of 400-500 lbs. per square. All vertical or exposed seams at perimeters and projections must be welded. On smooth or coated roofs, all laps/seams in the field, at perimeters, and projections must be welded. Picture framing concept must be used on all perimeters and projections.

**FLOOD & AGGREGATE:**

Flood Type: \_\_\_\_\_ Gallons per Square: \_\_\_\_\_

Aggregate: \_\_\_\_\_ Lbs. per Square: \_\_\_\_\_

The undersigned roofing contractor hereby warrants (a) that it has complied with Hyload's written specifications and recommended installation practices with respect to the job described herein, (b) that it has made such installation in a good and workmanlike manner, (c) that for a period of two years from the date hereof the roofing contractor shall, at roofing contractor's expense, provide labor to stop all leaks and/or correct any non-conforming conditions resulting from faulty workmanship and/or to meet the specifications of Hyload, and (d) that following passage of said two year period, unless under notice from Hyload of some defect, roofing contractor shall have no further obligation to make repairs at its own expense under this warranty.

Roofing contractor shall indemnify and hold Hyload harmless for all claims and expenses, including reasonable attorneys' fees, which arise from any breach of the warranties provided in subsections (a), (b) and (c) of this paragraph.

Roofing Contractor: \_\_\_\_\_

By: \_\_\_\_\_

Authorized Signature of Roofing Contractor

Date: \_\_\_\_\_

**TO BE COMPLETED BY HYLOAD, INC.**

Warranty Number Assigned: \_\_\_\_\_

Scope of this project has been reviewed and accepted by the Hyload Technical Department.

Accepted by: \_\_\_\_\_ Date: \_\_\_\_\_

Warranty being sent to: \_\_\_\_\_

Comments: \_\_\_\_\_

\_\_\_\_\_