

PROVIDE CONT. HEMMED
EDGE IN FLASHING.

WEEP HOLE AS SPEC.

3" LAP WITH BEAD OF
SEALANT AS SPEC.

SHEET METAL RECEIVER AS SPEC.

SELF-ADHERED MEMBRANE
SHEET CLOSURE SECURED
TO WALL WITH TERM BAR &
3 COURSE MASTIC
ENSURING PROPER OVERLAP

FASTENERS APPROX. 24" O.C.

3" LAP AT JOINT TYP.

PRE-FINISHED SHEET METAL
EXPANSION JOINT COVER AS SPEC.

EXTEND BASE FLASHING UP
AND OVER WOOD BLOCKING

REMOVABLE SHEET METAL
COUNTERFLASHING AS SPEC.

SEAL TOP OF FLASHING WITH A
3-COURSE OF VERTICAL GRADE PROOF
CEMENT AND REINFORCEMENT FABRIC
AS SPEC.

CONT. CLEAT AS SPEC.

EXTENDED FIELD PLIES
ABOVE HEAD OF CANT
STRIP

FASTENERS APPROX. 8" O.C.

HYBASE SAM FLASHING AS SPEC.

END LAP SPLICE STRIP 6" WIDTH -
CENTER OVER END LAPS OF FLASHING
AND HOT AIR WELD EACH SIDE

FLEXIBLE VAPOR RETARDER
WITH COMPRESSIBLE INSUL.

HYLOAD WS FLASHING AS SPEC.

HYLOAD WS FIELD SHEET AS SPEC.

WOOD CANT TO BRACE
CURB

MULTIPLE PLY SHEETS AS SPEC

EXISTING/ NEW ROOF DECK

COVERBOARD INSUL. AS SPEC.

T-CLEAR INSULATED BALLASTED
PAVERS OR OTHER APPROVED
BALLASTED INSULATION SYSTEM.
THICKNESS AS SPECIFIED.
IMPORTANT - CONTACT HYLOAD
FOR PROPER SECUREMENT OF
T-CLEAR SYSTEM.

THERMAL INSUL. AS SPEC.

BASE SHEET AS SPEC. AS REQUIRED



HyTOP™
Total Overhead Protection

NON-WALL SUPPORT PARAPET AT MASONRY WALL

CORPORATE HEADQUARTERS

5020 ENTERPRISE PARKWAY
SEVILLE, OHIO 44273
PHONE: (800) 457-4056
FAX: (330) 769-4153

DWG NO.

PMR005