

UNIT MOUNTING CURB AS SPEC.

SEALING MATERIAL AS SPEC.

WOOD NAILER AS SPEC.

10"
NOMINAL
FLASHING
HEIGHT

EXTEND FIELD PLIES
ABOVE HEAD OF CANT

EXTEND FLASHING UP & OVER AS SPEC.

SHEET METAL FLASHING RECEIVER AS SPEC.

HIGH-DOMED, CAPPED, GASKETED FASTENERS
(APPROX. 18" O.C. DEPENDING UPON WIND
ZONE AND LOCAL CONDITIONS; MINIMUM TWO
FASTENERS PER SIDE)

T-CLEAR INSULATED BALLASTED PAVERS OR
OTHER APPROVED BALLASTED INSULATION
SYSTEM. THICKNESS AS SPECIFIED.
IMPORTANT - CONTACT HYLOAD FOR PROPER
SECUREMENT OF T-CLEAR SYSTEM.

REMOVABLE SHEET METAL
COUNTERFLASHING

FASTENERS APPROX. 8" O.C. & 3 COURSE
ROOF CEMENT & REINFORCEMENT FABRIC AS
SPEC.

END LAP SPLICE STRIP 6" WIDTH - CENTER
OVER END LAPS OF FLASHING AND HOT AIR
WELD EACH SIDE

PLYSHEET FLASHING AS SPEC.

HYLOAD WS FLASHING AS SPEC.

HYLOAD WS FIELD SHEET AS SPEC.

HYBASE SAM INTERPLY FIELD SHEET AS
SPEC.

COVERBOARD INSUL. AS SPEC.

THERMAL INSUL. AS SPEC.

BASE SHEET AS SPEC. IF REQUIRED

EXISTING/ NEW ROOF DECK



HyTOP™
Total Overhead Protection

CORPORATE HEADQUARTERS

5020 ENTERPRISE PARKWAY
SEVILLE, OHIO 44273
PHONE: (800) 457-4056
FAX: (330) 769-4153

INSULATED AIR UNIT CURB (SELF-ADHERED APPLICATION)

DWG NO.

PMR007