

Description:

Hyload Mastic

A select blend of refined asphalt, aliphatic solvents, non-asbestos fibers and fillers.



Product Highlights:

Hyload Mastic

- Designed for general utility repairs on most roof systems.
- Cold applied by trowel.
- Resistant to UV and chemical attack.
- Meets current VOC requirements.
- Non-Asbestos.
- Cures to a tough, durable protective barrier.
- ASTM D4586, UL Classified.
- *For specifics consult the Hyload Technical Department.*

Applications:

- Detailing:
- Roofing Membranes
- Waterproofing membranes
- Masonry flashing Membranes
- Expansion Joints
- Cove Joints
- Parapets
- Weather Sealing
- Window and door Jams
- To repair bare spots, blisters, ruptures and splits.
- Waterproof concrete and Masonry surfaces

Packaging:

- 32 Oz. tubes
- 5 gallon Pails
- Black color

Substrates:

- All Hyload Membranes.
- Wood
- Metal
- Concrete, Block, and Masonry
- Glass
- Stainless Steel

Applicable Performance Standards:

- ASTM D4586
- UL Classified

Performance and Physical Properties:

Property	Test Method	Result
Wt/gal, lbs.	D6511	8.6-9.0
Solids % by wt.	D6511	75-80
		% by vol.
Viscosity, cps	Brookfield	1-1.5 MM
pH		N/A
Flash Point, °F	PMCC	105 min.
Color, uncured & cured	Visual	Black
Drying time, Touch	70 °F/50% R.H.	8 hours
Shelf Life	70 °F/50% R.H.	1 year
VOC	EPA Method 24A	250 gm/liter max.

Limitations:

- DO NOT use on 100% rubber or plastic substrates.
- DO NOT use on products containing coal tar.
- DO NOT use where this product may come in contact with potable water.
- DO NOT THIN
- EXTERIOR USE ONLY.

Cure Time:

- Initial 8 Hrs.
- Full 7 Days



Warranty:

Hyload makes available to its customers several high performance product warranties. Contact Hyload's Corporate Office directly for details. A standard warranty is 10 years.