

Description:

HYLOAD JAMB CLOSURE MEMBRANE

The Hyload Jamb Closure Membrane is an 8" or 12" poly-reinforced membrane, incorporating DuPont's Elvaloy® KEE polymer (40 mils) and 4" of rubberized asphalt (15 mils) with a silicone release paper.



Product Highlights:

- The Hyload Jamb Closure Membrane is a tough watertight sheet membrane that provides closure between air and vapor barriers and windows.
- The Jamb Closure Membrane can be used in residential, commercial and industrial applications. Recommended to adhere all Hyload membrane systems
- Not effected by high alkaline environments typical of masonry construction
- Hyload Systems will not deteriorate or harden with longevity or ultra violet ray exposure
- Hyload's Technical Service Department offers specialized advice through a highly experienced technical staff to aid the construction process.
- Hyload provides architectural design service, contractor training and job site assistance
- Lifetime Building Warranty available when total Hyload flashing system is used.
- ***For specifics consult the Hyload Technical Department.***

Applications:

- Through-Wall Masonry Flashing
- Door Jam Flashing
- Window Jam Flashing
- In conjunction with Hyload Pre-Formed Shapes
- Building Envelope Flashing

Packaging:

- Standard Widths:
- 8" x 75' and 12" x75' Rolls

Substrates:

- All Hyload Membranes.
- Wood
- Metal
- Concrete, Block, and Masonry
- Stainless Steel

Colors:

- Black, Gray, and Tan



Limitations:

- Hyload Jamb Closure Membrane should not be applied to moist or damp surfaces.
- Hyload Jamb Closure Membrane should only be applied when both air and surface temperatures are 32°F and rising.
- Hyload Jamb Closure Membrane cannot be used with coal tar mastic or polysulfide sealant.

Performance and Physical Properties:

Property	Test Method	Results
Elongation	ASTM D412	175%
Tensile Strength	ASTM D412	650 psi min
Tear Strength	ASTM D624	280 ppi
Low Temperature Flexibility	ASTM D146	0° Pass
Water Absorption	ASTM D471	<0.1%



Warranty:

Hyload makes available to its customers several high performance product warranties. Contact Hyload's Corporate Office directly for details. A standard warranty is 10 years.