

PRE-FINISHED METAL JOINT COVER PLATE
6" WIDE MIN. - SET IN TWO BEAD OF
SEALANT AS SPEC.

PRE-FINISHED BALLAST COVER PLATE

T-CLEAR INSULATED BALLASTED PAVERS
OR OTHER APPROVED BALLASTED
INSULATION SYSTEM. THICKNESS AS
SPECIFIED. IMPORTANT - CONTACT
HYLOAD FOR PROPER SECUREMENT OF
T-CLEAR SYSTEM.

FASTENERS AT
APPROX. 3" O.C.
STAGGERED

4" WIDE
FLANGE APPROX.
3" MIN.

3" MIN. HYBASE SAM FLASHING STRIP AS
SPEC.

HYLOAD WS FLASHING HOT AIR WELDED
AT EACH END AS SPEC.

END LAP SPLICE STRIP 6" WIDTH - CENTER
OVER END LAPS OF FLASHING AND HOT AIR
WELD EACH SIDE

PRE-FINISHED METAL "GRAVEL STOP" SET IN
ROOF CEMENT; PRIME METAL FLANGE WITH
ASPHALT PRIMER

HYLOAD WS FIELD SHEET AS SPEC.

HYBASE INTERPLY FIELD SHEET AS SPEC.

COVERBOARD INSULATION AS SPEC.

THERMAL INSULATION AS SPEC.

BASE SHEET AS SPEC. IF REQUIRED

EXISTING / NEW ROOF DECK

EXISTING / NEW WOOD
NAILERS AS SPEC.

EXTEND PLY SHEET
MEMBRANE BELOW BLOCKING

CONTINUOUS CLEAT AS SPEC.

CONTINUOUS BEAD OF
SEALANT AS SPEC.



HyTOP™
Total Overhead Protection

ROOF EDGE

CORPORATE HEADQUARTERS

5020 ENTERPRISE PARKWAY
SEVILLE, OHIO 44273
PHONE: (800) 457-4056
FAX: (330) 769-4153

DWG NO.

PMR006

